



DIMENSIONS = FEET

NUMBER OF LANES	R/W BEHIND SIDEWALK		SIDEWALK		PLANTING		BIKE LANE		LANE		LANE		SWALE*		LEFT TURN		CLEAR ZONE		RIGHT OF WAY		SEE STANDARD DRAWING 4-6A FOR MINIMUM STRUCTURAL DESIGN AND STREET CROSS SLOPE DESIGN	SEE MINIMUM STREET DESIGN STANDARDS TABLE FOR ADDITIONAL DESIGN ELEMENTS
	A	B	C	D	E	F	G	G	*G1	H	H	ROW	ROW	ROW	ROW	ROW	ROW	ROW	ROW	ROW		
2 LANES	1	6	8	5	10	0	14	0	0	4	80	80	80	80	80	80	80	80	80	80	ADT	3,000-14,000
3 LANES	1	6	8	5	10	0	0	11	0	4	80	80	80	80	80	80	80	80	80	80		
4 LANES	1	6	8	5	10	10	14	0	0	4	96	96	96	96	96	96	96	96	96	96		
* INCLUDES CURB; SEE STANDARD DRAWING 5-12C FOR LID SWALE DETAILS																						
** G1 = COMBINATION CENTER LEFT TURN & MEDIAN																						
2 AND 3 LANE BOULEVARD STREET SECTIONS MUST MAINTAIN ≥ 18 FEET FROM CURB FACE TO MEDIAN																						

APPROVED BY	REVISED DATE	CITY OF OLYMPIA MAJOR COLLECTOR BOULEVARD WITH LID SWALE	STD. DWG. NO.
FRAN R. EIDE, PE CITY ENGINEER	8/30/2018		4-2F-LID