



SECTION VIEW PLANTING DETAIL

NOTES:

1. ALL TREES SHALL MEET ANSI AZ60.1 AND OMC 16.60 STANDARDS.
2. LOOK FOR EXCESSIVE SOIL ON THE ROOT BALL COVERING ROOT FLARE AND REMOVE TO EXPOSE ROOT FLARE.
3. BOTTOM OF ROOT FLARE SHALL BE AT FINISH GRADE IN WELL DRAINED SOIL AND 2" ABOVE FINISH GRADE IN POORLY DRAINED SOIL.
4. B&B TREES: COMPLETELY REMOVE WIRE BASKET AND TREATED OR SYNTHETIC BURLAP AND TWINE. REMOVE NATURAL TWINE AND BURLAP FROM TOP AND SIDES OF ROOTBALL.
5. CONTAINERIZED TREES: SHAVE THE OUTER 1-2" OF SOIL FROM ROOT BALL WITH SHARP KNIFE.
6. GROW BAG TREES: REMOVE BAG COMPLETELY.
7. STAKE ONLY IF REQUIRED BY PROJECT FORESTER OR NECESSARY FOR TREE STABILITY. REMOVE STAKES AFTER 1 YEAR.
8. PRUNE DAMAGED OR BROKEN BRANCHES. NO OTHER PRUNING SHALL BE DONE AT PLANTING.
9. SEE STANDARD DRAWING 4-49 FOR TREE GRATE REQUIREMENTS.

APPROVED BY	REVISED DATE	CITY OF OLYMPIA	STD. DWG. NO.
FRAN R. EIDE, PE	11/8/2018	TREE WELL WITH GRATE PLANTING DETAIL	4-52
CITY ENGINEER		(ADEQUATE SOIL)	